

AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report(s). This authorization also applies to the Multiple Listee model(s) identified on the correlation page of the Listing Report. This document is the property of Intertek Testing Services and is not transferable. The Certification Mark(s) may be applied only at the location of the Party Authorized to Apply Mark.

Applicant:

DKS Steel Door and Frame Systems, Inc.

2142 Tubeway Avenue Commerce CA 90040

Country:

Contact:

Dave Kesler

Phone:

323-888-7763 323-888-0552

Fax: Email:

dkesler@neo.rr.com

Party Authorized to Apply Mark:

ditoolor@nooinnoo

Evaluation Center:

See following page(s)
Intertek (Middleton)

Control/Client Number: 214173

Authorized By:

Thomas J. Patterson, Director of Certification

Intertek Testing Services NA, Inc. 545 E. Algonquin Road, Ste H, Arlington Heights, IL 60005 USA Phone 847-439-5667 Fax 847-439-7320



Intertek

This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Testing Standard{s}:	indard{s}: :NFPA 252 (2008):UL 10(c) (2009):CAN / ULC S104 (2010):NFPA 252 (2012)	
Product: DKS 90 Minute Fire Rated Steel Louver		

ATM for Report 100838066MID-012

ATM Issue Date: 07/16/2014

Listing Section(s): DOOR & FRAME HARDWARE

CSI Code:

08 90 00 Louvers and Vents

Description:

Product Covered:

DKS 90 Minute Fire Rated Steel Louver

Product Description:

DKS Fire Rated Steel Louver for use in listed and labeled fire rated hollow metal door applications, positive and neutral pressure.

Rating	Maximum	Maximum	Maximum	Door
	Area	Height	Width	Type
Up to 90 Minutes	288 sq. in.	12"	24"	Steel

Tested and qualified per UL 10C (2009), NFPA 252 (2008), and CAN/ULC S104 (2010).

See manufacturer's installation instructions for additional information, restrictions and limitations.

See code requirements for additional general restrictions and/or limitations in regard to louvers.





DKS 90 Minute Fire Rated Steel Louver

Series: YLV and VLV Steel Louvers

Product description:

DKS Fire Rated Steel Louver for use in listed and labeled fire rated hollow metal door applications, positive and neutral pressure.

Rating	Maximum Area	Maximum Height	Maximum Width	Door type
Up to 90 Minutes	288 sq.in.	12"	24"	Steel

AVAILABLE INVENTORIES WITH 90 MINUTE FIRE RATING

YLV Series

Item No	Sizes		A 1100
	Width	Height	Area
YLV1212	12"	12"	144 sq.in.
YLV1812	18"	12"	216 sq.in.
YLV2412	24"	12"	288 sq.in.

VLV Series

Item No	Sizes		Araa
	Width	Height	Area
VLV1212	12"	12"	144 sq.in.
VLV1812	18"	12"	216 sq.in.
VLV2010	20"	10"	200 sq.in.
VLV2412	24"	12"	288 sq.in.

Cal-Royal Products, Inc.